

AMENDMENTS TO THE SPECIFICATION

10/509840

Please insert the following paragraph beginning at page 5, line 29, after the title
"Brief Description of the Drawings":

The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

Please replace the paragraph beginning at page ~~4~~⁵, line ~~3~~⁵, with the following
rewritten paragraph:

RP
11/14/06

According to an aspect of the present invention to achieve the second objective, in addition to the light guiding panel described above, there is provided a backlight apparatus using the light guiding panel having recesses formed thereon of any one of claims 1 through 7, comprising: a tube optical source which is arranged parallel to and along at least any one side or both sides of the light guiding panel, and if electric power is supplied, generates light so that the light is incident into the light guiding panel through the side of the light guiding panel; a reflection ~~portion~~ ^{portion} which surrounds the optical source such that the light of the optical source is reflected into the light guiding panel; a bottom surface reflection plate which is attached to the bottom surface of the light guiding panel so as to reflect light which passes through the bottom surface, back into the light guiding panel; and a side reflection plate which is attached to sides of the light guiding panel, at which the optical source is not installed, and reflects light incident on the side reflection plate into the light guiding panel, wherein without placing a diffusion sheet on the front surface of the light guiding panel, the backlight apparatus is used as a backlight for a transparent or translucent printed film or a liquid crystal display (LCD) unit.

Please replace the paragraph beginning at page 5, line 22, with the following
rewritten paragraph:

Preferably, the backlight apparatus further comprises an assembly frame which accommodates the light guiding panel, the tube optical source coupled with the light guiding